

SBH-5

Three-Dimensional Mixer



**EQUIPMENT
TECHNICAL PARAMETER**

南京翰洋智能设备有限公司
NANJING HANYOO PHARMATECH CO., LTD.



SBH-5 Three-Dimensional Mixer



MACHINE APPLICATION

The three-dimensional motion mixer is widely used for mixing dry powder materials in pharmaceutical, chemical and food industries. It is a sterile, dust-free, fully enclosed, high-efficiency and energy-saving powder mixer. It can also quickly and evenly mix several materials with different specific gravity and particle size. The machine uses the unique alternating pulse motion to continuously promote the mixing of materials. The eddy current

produced by the machine has a variable ability gradient, so as to produce excellent mixing effect. The machine also has the advantages of stable operation, low noise, high loading system and short mixing time. The machine through mechanical transmission, make the S-type mixing paddle rotation, push the material reciprocating flip, uniform mixing, operation using electrical control, can set the mixing time, when the automatic stop, electric pouring, so as to improve the mixing quality of each batch of materials, to achieve high uniformity of mixing.

MACHINE FEATURES

1. the inner and outer parts of the machine are made of 304-2b stainless steel, and the barrel is made of 3042b stainless steel, with a material warranty.
2. the materials have no centrifugal effect, specific gravity segregation, stratification and accumulation in the mixing process. Each component can be evenly mixed under a wide weight ratio, and the mixing rate is more than 99.9%.
3. the charging coefficient is high, which can reach 80% (only about 40% for ordinary mixers) and the mixing time is short. It is an ideal product among all kinds of mixers at present.
4. the structure of the equipment is compact, and the transmission part adopts stepless speed regulation (frequency conversion or electromagnetic speed regulation), which is very convenient to operate.
5. all parts of the barrel are arc transition, and have been precision polished to meet the GMP requirements.
6. the electrical control to be mixed shall be mechatronic. The mixer is equipped with an adjustable timing device, which can be set by the user according to the mixing time required for each batch of products, and will automatically stop after the work. Both sides of the mixer are equipped with inching devices, which further reduces the operation difficulty of workers.

Principle and characteristics

1. the machine uses the unique three degree swing, driven by the driving shaft, to make a cycle of translation, rotation and rolling and other composite movements, which promotes the material to make a three-dimensional composite movement along the cylinder, so as to realize the mutual flow, diffusion, accumulation and doping of a variety of materials, so as to achieve the purpose of uniform mixing.
2. the mixing cylinder of the machine moves in multiple directions, and the materials have no centrifugal force, gravity segregation, stratification and accumulation. Each component can have a very different weight ratio, and the mixing rate can reach 98%. It is an ideal product of all kinds of mixers at present, with large cylinder loading rate, high utilization rate, short mixing time, high efficiency and no temperature rise during mixing.
3. except that the transmission system and the frame of the machine body are made of A3 steel, the others are made of high-quality stainless steel.

TECHNICAL PARAMETER

MODEL	SBH-5
Barrel volume (L)	5
Max. loading volume (L)	3.5
Max. loading weight (kg)	3.5 kg/batch Max
Spindle speed (r/min)	12 rpm; frequency control
Reducer (WPA)	60
Motor power (kw)	0.75kw (220V)
Mixing time	8-15min
Overall dimension (L * w * h) (mm)	850x900x1050
Weight (kg)	120

ELECTRONIC PART LIST

NO.	NAME	MODEL& SPECIFICATION	MANUFACTURER
CONFIGURATION LIST			
1	Barrel	Stainless steel $\delta 2.0$ mm	WUXI
2	Sealing Plate	Stainless steel $\delta 1.2$ mm	WUXI
3	Frame	A3	NANJING
4	Electrical Machinery	0.75kw	NANJING
5	Reducer	Wpa60	CHANGZHOU
6	Chain	A3	HANYOO
7	Feed Inlet	DN 100 (According to the bucket)	HANYOO
8	Discharge Port	DN 50 (According to the bucket)	HANYOO
9	Swivel Arm	$\delta 6-20$ mm	HANYOO
10	Circular Solitary Plate	304	HANYOO
11	Acne Board	A3	HANYOO
12	Main (driven) Shaft	A3	HANYOO
13	Pin shaft		HANYOO
14	Wrist shaft	Stainless Steel	HANYOO
15	Coupling	Stainless Steel	HANYOO
16	Pulley	Stainless Steel	HANYOO
17	Gland	A3	HANYOO
18	Shaft Housing Bearing	4	HARBIN
LIST OF ELECTRICAL APPLIANCES			
1	Circuit Breaker	DZ47-60A 3P C60	CHINT
2	Circuit Breaker	DZ47-60A 1P C10	CHINT
3	Contactor	CJX2-1210 220V	CHINT

NO.	NAME	MODEL& SPECIFICATION	MANUFACTURER
4	Emergency Stop Button	NP2-BS542	CHINT
5	Operation Button	NP2-BD25	CHINT
6	Signal Lamp (Red)	DN16-22BS/4 220V	CHINT
7	Signal Lamp (Green)	DN16-22BS/4 220V	CHINT
8	Time Relay, Time Relay	DH48S-1Z	CHUANGYO TECHNOLOGY
9	Electric Appliance Wire		CHINT
10	Inverter	0.75kw	UPPER DRIVE UNIT

The banner features a dark blue background with several white line-art icons related to medicine and healthcare. These include a blister pack of pills, a medicine bottle with a cross, a single pill, a pill being poured from a container, two pills, a syringe, and another blister pack.

HANYOO

翰洋科技

Add:No.380 Sanqiaogeng,Gaochun District,Nanjing,China

Tel:+86-025-5621 6295

[Http://www.hanyoopm.com](http://www.hanyoopm.com)